


HG4000

HORIZONTAL GRINDER


EU CONFIGURATION



JOBSITE SAFETY. The Thrown Object Deflector (TOD) reduces the amount and distance of thrown material debris, while also reducing interference when loading over-length material.



OPTIMAL CUTTING PERFORMANCE. The patented Series II duplex drum offers proven cutting performance, and reversible hammers and tips nearly double the wear life of single-sided designs and simplify daily maintenance. The optional chip drum produces a consistently chipped end product, rather than traditional shredded material, for uses such as biofuel.



ENGINE POWER. The Fiat Powertrain Technology (FPT) Tier 4 Final engine provides 515 hp (384 kW) of power to meet your jobsite demands.



PRODUCT SIZING. The dual-screen design, along with several screen options, helps boost processing efficiency while controlling end product sizing needs.



PROGRESSIVE PROCESSING. The patented SmartFeed system monitors engine rpm and adjusts grinding speed to increase productivity. The open-ended, wide infeed table makes material loading easy and efficient.



JOBSITE EFFICIENCY. Operation and maintenance are simple with easy access points to the radiator, the optional screen hoist and optional hydraulic stabilizers.



VERMEER.COM



EQUIPPED TO
DO MORE.

HG4000 HORIZONTAL GRINDER EU CONFIGURATION

GENERAL WEIGHTS AND DIMENSIONS

Weight: 22.000 kg (48,500 lbs)

Max transport length: 9,4 m (31')

Max transport width: 2,5 m (8.2')

Max transport height: 4 m (13')

ENGINE

Make and model: Fiat Powertrain Technology C13 Tier 4F

Max gross horsepower: 384 kW (515 hp)

Fuel tank capacity: 738.2 L (195 gal)

INFEED CONVEYOR

Feed table width: 152,4 cm (60")

Feed table length: 4,6 m (15')

Loading height: 2,3 m (7.6')

INFEED ROLLER

Max feed height: 66 cm (26")

Diameter: 71,1 cm (28")

DUPLEX DRUM OPTION

Millbox opening: 152 x 66 cm (60" x 66")

Drum diameter: 57,2 (22.5")

Number of hammers: 9

Number of tips: 18

CHIP DRUM OPTION

Mill box opening: 152.4 cm (60")

Drum diameter: 69.3 cm (27.3")

Depth of cut: Ranging from 3.2 mm to 25.4 mm (.125" to 1")

Number of knives: 24

DISCHARGE SYSTEM

Belt length: 21,7 m (71.3')

Belt width: 121.9 cm (48")

Belt design: 3-ply – 330# with V-cleat

HYDRAULIC SYSTEM

Tank capacity: 227.1 L (60 gal)

Implement pump type: Variable displacement, axial piston

Discharge conveyor pump: Fixed displacement, gear pump

CONTROLS

Stationary: Side-mounted LCD control station

Remote: Multifunction with built-in LCD display; max 91,4 m (300') operating range

OPTIONS

Vermeer Confidence Plus® asset protection program

Special paint

Air compressor

Screen hoist

Screen sizes

NOTES:

Vermeer Corporation reserves the right to make changes in engineering, design and specifications; add improvements; or discontinue manufacturing at any time without notice or obligation. Equipment shown is for illustrative purposes only and may display optional accessories or components specific to their global region. Please contact your local Vermeer dealer for more information on machine specifications. Vermeer, the Vermeer logo, Equipped to Do More and Vermeer Confidence Plus are trademarks of Vermeer Manufacturing Company in the U.S. and/or other countries. Fiat Powertrain Technology is a trademark of FPI Industrial S.p.A.

© 2018 Vermeer Corporation. All Rights Reserved. Printed in the U.S.A. Please recycle.

